



NOTE: ALL INFORMATION NOT READ TO MANUFACTURE LOW 280-11 99-15




MOTE: MILL INTORMA JA NOT P 3. 5
MANUFACTURE LOWEST11 FOR NEF INFO DALY.





NOTE: PLL INFORMATION NOT READ TO MANUFACTURE LDW 280-17789-13,-151-17 IS FOR REF INFO DALY. ON LDW 280-51587 -1. INSTE REMINE (REPLACE MS20470-104(2) -15 (7HOLES) IN LDW280-17789-FINISH: #88 (ANOBIRE) /LSF 14- 9036 ILT = E 183- E SPLICE ADD OF -LDW 280-17289--11-1 7396-13#-14(Rtt) MS 20470-804(2) ON LOW 280: 5/587-1488/L - REWORK EXISTING LDW230-17789-11 TO CREATE -11-1


*** IDENTICAL EXCEPT PS WOTED *** MIN LDW28051587, REMOTE MALOW 280-\$1587 FKOM-11. LM-1(31) (I REGINA) -ENISTING RIVETS (REF) SECT A-A (SHU) . THIS IS AN ORIGINAL E.D. SECT B-B (OPP) COLUMN SECTION COMES ENGINE COMES DE LONG TORM ON THE CONTROL OF T NAS 9-1100 MODEL PROCURENT ACT NO. SACC LINEY INC. SUB-OBSTR LINEY IN LM-1(31) . BRACKET ~ D. S. ~ He PRESS LDW280-17789 SYSTEM TEST POINTS PAGES - 6954 NO MAROCERS A STRAIGHT MEN DES VINT.


NOTE: OLL INFORMATION NOT READ TO MANUFACTURE LDW 280-17789-13,-154-17 IS FOR REF INFO DALLY.













UNLESS OTHERWISE SPECIFIED TOLERANCE ON PLANSES IS ± 1/32 LESSATION OF AUL HARD & HE AL ALY HOUTS SHOUTH THOSE I PRICE AND SPECIFIED THOSE I PRICE AND SPECIFIED THE PRICE AND











1.0	500P8 1	This drawing satu temperature cont	abliance the requirements for the application of an eluminum pigmented forf57ER esta based finish coating for redistive rol purposes.							
2.0	APPLICABLE DOCUMENTS:	The following documents shell be applicable to the extent specified herein:								
		Covernment	,							
		MII-T-6094A	Thinner, Dape and Lacquer (Cellulose-Hitrate)							
		TT-L. 735a .	Isopropyl Alcohol							
		MIL=M-45202A	Magnesium Alloys, Anodic Treatment of							
		Garantin a								
		LEP-14-4100	Equipment and Fac. lities for Surface Preparation and Application of Organic Finishes							
		LET-14-9010	Chemical Conversion Film, Alodine 1200 on Aluminum and Aluminum Alloys							
		LSP-14-9012	Chemical Conversion Costing for Magnesium and Magnesium Alloys							
		LSP-14-9030	Anodic Costing (Type I - Chromic Acid) for Aluminum Alloye							
3.0	REQUIREMENTS:	control purposes,	drawings or specifications require the application of aluminum pigmented efficient resid based finish for radiative temperature, possessing a solar absorbance of 0.18 to 0.23 at not provided a solar absorbance of 0.18 to 0.23 at not provided in accordance with the following:							
3.1	SPECIAL REQUIREMENTS:	seme materials, 1	anel shall accompany each batch lot of parts or assemblies to be finish coated as outlined herein. These panels shall he of the receive the same preparation and be finish costed under the prevailing conditions of the production batch lots. The finished pan lad with the batch lot or assemblies and forwerded to Quality Control Laboratory for testing as per h.O							
3.2	MATERIALS:	The following am	terials are approved for use:							
-		(s) "Cet-A-Lac"	Earies 600 Temperature Control Paint							
		(1) Alumin	um Pigmented, Non-Yellowing Base, No. 643-1-1							
			mint and Chemical Co. e, California							
	,	(b) Cleaner (1) Lacquer (2) Isoprop	r Thimmer par NIL-7-609AA, Source open pyl Alcohol par TT-1-75s, Source open							
3.3	EQUIPMENT:	Equipment and fuc	cilities for preparation and application of material specified herein shall be in accordance with LSP-14-5100.							
3.4	PROCEDURE 1									
3.4.1		Surface Prepareti	ion and Pretrestment - Surfaces to be finish coated in accordance with this drawing shall be prepared as follows:							
		(a) Aluminum All	loys - Aluminum alloy surfaces shell be anodized per LEP-14-9030 or alodined per LEP-14-9010.							
			GRUMMAN AIRCRAFT ENGRG CORP., BETHPAGE, L. I, NEW YO							
			SIZE CODE IDENT NO. B 26512 LDW280-17869							

3.4.1	(Continuted)	(b) Magnesium Alloys - Magnesium slloy surfaces shell be pretreated with a Type III Dichromate (Dow \$7) treatment per LEP-10-9912.	
2	(,	or Anodised (now \$17 Trestance), per MILH-45202B, Type II, Class D. The pretrected surface shell then be primed with an epoxy polyamide primer per LEF-14-4305.	
		(c) Fiberglass - Prior to application of the finish cost, the fiberglass surfers shall be lightly sended with f820 or finer wet-dry sbrasive paper. The manded surface shall be wiped with languar thinner per MILWI-6094 after sanding.	
		(d) Polycerbonate Plastins - Prior to application of the finish coat, the polycerbonate surface shall be lightly sanded with \$320 or finer vet-dry shraitve paper. The sanded surface shall be wiped with isopropyl slochol paper TT-I-735a.	
3.4.1.1		Where s time lapse of 24 hours or greater occurs between pretreatment and finish coat application, or where contemination is evident, pur shall be solvent cleaned with lacquer thinner MIL-T-6094 prior to application of finish coat,	ta
3.4.2	PREPARATION OF COAT	INO MATERIAL:	
		Throughly agitate the base components prior to use. Combine three (3) parto by volume of 'ase coating to 1 pert by volume of catelyst solution. Stir to a uniform mix. Allow the mixture to stand a minimum of 30 minutes before applying. The mixture shall be used without further thinning. The usehin put if an of the mixture is supported by thours.	
3.4.3	APPLICATION:	Apply by spray, one light cost of topcost and allow to sir dry for 1 hour. Apply by spray, one wet crosscost, taking care to achieve complete coverage. The finished topcost shall have a total dry film thickness of 1.0 + 0.2 mile. Air dry, at room temperature, for a minimum of 48 hours before handling. An accelerated cure of the finish may be achieved by air drying at room temperature for a minimum of 2 hours and then baking at 200°F for 4 hours.	ıf
3.5	REPAIRS:		
3.5.1		Small Damaged Areas - After the finish coat is thoroughly dry, the affected area shall be touched up by brush application.	*
3.5.2		Large Damaged Areas - After drying finish coat a minimum of one hour, the entire surface shell be resprayed in scordanco with this drawi Allowable thickness buildup of repaired sreas shall not exceed 2 mile average maximum.	ng.
4.0	QUALITY ASSURANCE PE	NOVISIONS: Quality Control shall be responsible for assuring compliance with the requirements of this drawing.	
4.1.1		Visual Inspection - The cured topcost shall have a smooth unifors finish that completely covers the surface to be coated. The finish coabe free of any blistering and/or excessive orange peel.	t shal
4.1.2		Adhesion Test - Dry tape test	
4.1.3		Radiative Characteristics property and a respect to the control of the control property of the control shall be determined to the control test panel of the control test panel property of the control test panel. Perhaps between the solutions and the secured with a Characteristic measurement, and the secured with a Characteristic measurement. The radiative characteristic measurement taken, date of measurement, and locatic of measurement. The radiative characteristics subtituted by the sunject finish shall be as specific paragraph 3.0.	The ents
1.2		Parts not meeting the requirements of this drawing shall be rejected or subjected to Materials Seview Board Action.	
		GRUMMAN AIRCRAFT ENGRG CORP., BETHPAGE, L. I., N	VEW YO
		SIZE CODE IDENT NO.	_
		B 26512 LDW280-1786	2
		SCALE SHEET 3.	00












THIS IS AN ORIGINAL DWG







			207	168-19/2				WEIGHTS VI A MAN				SCAL			SHEET 1.0	
	SH NO. USED	-21	PRIM NO.	K/ooi)		CLASS I ENGRG CHA	MGE	STRUCTURE LEGICALINA				15 B	1 2651	2 μ $^{\prime\prime}$	280-178	02 1
LAST SEC	T LTR USED			MAN REL INFO	08	CLASS II ENGRG CH	ANGE	STRUCTURE WALLS		ROJ ENGR PL	unkett 13 hun	14 SE B	2651	10. C44		
REV						DETAIL SPEC REQUIR	EMENT	MEH DESINTALES				TE	DUIPMEN	T-EN	D CLOS	JRE
SHEET		_	+	+-+	\dashv	ORIG DWG A		GR LEADER Stug	~ C5/s/cc			DES	CENT ST			FIC
REV					\dashv	± /32 ±.020	11/2°	CHECKED BY J 5 5.	3-66				A	NGI	E	
REV SHEET	B B	BB	-	+	\rightarrow	FRACTIONS - DECIMAL	S - ANGLES	LAYOUT BY C. DE					BETH	PAGE, L. I.	, NEW YORK	
SHEET	1.00 1.10	2.00 3.0	00			DIMENSIONS ARE IN TOLERANCE UNLESS		DRAWN BY J.COBB	5-2-66 R	ELIABILITY	S	(R)			T ENGRG CORI	,
	STATUS: FOR D			DQ SH		UNLESS OTHERWISE S		CONTRACT NO. NA			LIME ITEM	#			ON TYPE II	
011 5																(5)
		_		L	ENO ITEM					END ITEM					51-2	END ITEM
ART NO.	DW 280	-1788	5-23,25	GAEC SCH NO.	OR	PART NO. LOW	1280-1	7885-15,-16,-17	GAEC SCH NO	OR	PART NO.L DV	V280-	17885-2	27	GAEC SCH NO.	OR
	R END ITEM		T ASSY	OR SER NO.	MODULE	MODEL ON LITE		NEXT ASSY	OR SER NO.	REQD PER MODULE	MODEL OR		NEXT AS		OR SER NO.	REGO PEI
				MODULE	REGO PER	1			MODULE						MODULE	
LN	4	I DW28	2-23579	LTA-3(13)		LM.		DW290-23702	LTA-3(13)	IEA	LM		DW280-	23579	UA-3(13)	2
			-	LTA-3 D/R(46	-	 -							+	—	LTA3D/RC4	
	_			LM-3 (33)	<u> </u>	.	\rightarrow				-				L M-3(33)	
<u>'</u>	-			LM-4(34)		1	\rightarrow						1		LM-4(34)	-
	-			LM-6 (36) LM-5 (35)	-								+		LM (36)	
_	-		 	LM-7(37)		T DM 58	0-178	385 - 19-21					-		LM-7(37)	
				LM-8(38)		LM		DW280-23579	LIN-3(13)	1 LEA					LM-8(38)	
				LM-9(39)		LM		DW280-23579							LM-9(39)	_
					-	1.14	-+.	DW390 32530	114 5/23	1.54					LM-10(49)	-
—	-			LM-11(4)		+	\rightarrow						+		LM-11(41)	-
			<u> </u>	L M-12(42)	-	ļ	\rightarrow						-		LM-12(42)	_
	 		← —	LM-13143		ļ	_								LM-13(43)	
	M	LDW 280	1 23319		150		\rightarrow		-	-			1		LM-14(44)	-
	101	LDW/28	2-23579	LM-1545 LM-14(44	1 EA	+					LM		LUW 200-	233 19		- 4
LI		Duige	22570	LAAJEAE	157						LM		LDW280-1		LM-15(45)	2
						1		4			LM		I DW 28 O	22570	TM-5/R(65)	-2
						1		DW28017865					_			
				1				🔀							·	
						1		181			C.					
								lool			1		1		1	
-				ļ		1		IQI			-		ļ			
			•			-		[도]					1			
				-	_	-		1801			-					
				 	_	1		1 00					 			
				 		1		1 1 1 1 1 1 1								
						1		امرا					1			
								-								
								1 20								


O 1 MA: 1400


GRUMMAN AIRCRAFT ENGINEERING CORP. DATE LEUZBO BORDS B


2 4 4 8 8 8 8 C7	
West And	
55E DW6.	
55. NO. * 55. NO	11898-15 11873-11 11873-15 11854-15 11854-15 11854-15 11854-15

PKG 21 0 S	N. S.	と	PUNITURAL KARING	の	THE PERSON IN TH	250280 963	26 200	GROUP NO. 3330 PLES
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ON - * ANDED TM-5/R REQUIREMENTS	A. A. S.	S. S	2000		THE DEWING		X3352 SECTION VEH. DES, INT.
A THE PROPERTY TO THE PROPERTY OF THE PROPERTY	DEQUIREMENTS		BPHETINTY CO.	CHARTEN SECTION OF CHARTEN	TM-5/12/4			5-17-68 E. RANSOM (6. HANSMANN
	day		-	Í	1	117	1	2117


INS 9 - 1100









O 1 NAS 9-1100







	20 520	10:5				_Are De	∌-	6	T-40		<u> 24</u>
	1 2					A	=	ļ		Litt Lors the	
	LT 47 "		1			1-5	₹4.	ġ.		李建"山原"里	
		N: #2						4			
								4			
			_								
		3 3-				_4-11	===	Ţ.	- Mars 2 -	-52 n = 7 L + + 34	
		1 - 200	- 1					4	_> _=		
			3				Ē4	0	_Dv =-	-25 - 10 - 20 -	
		L 62 200									
					•				-		
		_ 4.		d	4	_a		9		- I Brester	트
					4						
					- M			á.			
		1_h1		_965	リテリリルド	しきいい	=1		JA. F -	- CATET LA TEM	-1 = 2
							=,	-			
								9			
		L 1						9	- M 10 E -	-5-19 1 A . 19 . 19 . 19 . 19 . 19 . 19 . 1	Ez
								9	- M. C.	A . 15.	= 2
					*	T C. WE	= .				
				_965	DUBLE		ĒŁ				
		1_h:		_00	していいかに	しからいる	==	1	JA., 4" -	TATE LA TEM	- 1 = Z
				265	している	_m-5/65	=1	1			
		1_h: :-		265	リデリーツー	していい		1	JAn Pr	TATE LA . EU	1 12
								4			
		- 4.		4	4	_a	主人				
								9	-		
									-		
					•	1 games	===		*-110° W	To million	01 = 4
		12 12 2				A	E-		*: A + 0" W		91 = y
		12 75 21				レルーコーラ	==		*: A + 0" W		At Dy
		12 mg 20				レルーコーコ			- 14 mm w		or Ex
		. 6 22									
				-				4			
		L - 200	-			-	=4	4	_> _=:		1 54
			- 1								
						Amilyan	=:	5	- 10 mg .	-F2 - F + + + 74	1 = 1
		1 3-				-11-	2.0	0	- Note:	一門上門中門 上京 五十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二	
								t			
						and the ".	= 1	-	- Maria -	- 1 m - 1 m - 1 m	
		,				A-Trace	E	1	- M		+
		Later and the					=4			No 1	
								4			
						45.00	=74.	1			
	T T	_A1 1 272				-A-2.22	-L	1			i) Di
	1 7 .0		7				T/	Ā	The 187 A		
	1 - 4	1 100	1			1-0-1	E4 .	ė.	L-70		EZ
	·							Š.	4	-	-/ -1
								i	70. 521		** ***
		TW = ===				_A	-	0		The state of the s	-)
								,			
	-1 - 57 6	1 4 - ==	(_Arm Day	===	(P		- Bo -	1 24
										17	
		- 1 A- 3			0	-A	= 4.	d	LTATE	ニー・ニー しかいきこ	1 = 1
		1_A- =						7 _			
#	1	170 -	7	1	TA CELE	-	===				= 4
	THE . TESA:	L 4 2 4		1				à			
5.1	1			11	-,, -, -, -, -, -, -, -, -, -, -, -, -,	_w= ==:		1 40	714. 77. 0		
- 4	1.3			_1,/	W. T. C. T.	_A		3 - 928	10 223	- Table - Table -	= = = =
							-	9		4000LE	
MODEL OF THE TEST	WET-SEE	MUME	- FEET - FEET	MODEL OF ESC TES	ETY" 500	MODLE	EX SE	MOSE IF BE	TES CET 4		100 39
MUSEL OF THE 1229	ALL STATE	B 355 W.		WHITE IF IN 1915	€EL. 423	F 55 W		MITTER SA THE	itte fit 4	T. BER	
			MODELE :				ACCURAGE.				
FE		第三 歌 作	77	HART OF		30 €2. 35E		3007 17		BECEN BE	
		Affine AND Was	OF (attain our Re.	子	PART AL			E E
								£	:	.= 515	
	=		THE 1554		E		EN 1554	1 11 11 .	3/24 - E-	- = = = = = =	王 理
		ul .						to the second			
											=
								-			
B. E. JUIL IR	EZMANO LE ZE	THE ST	6.5	MES SEME PENE	CONTRACT BY			TAE LESS		DECEMBER LETTER THE	
		ATUE. AT			Paratibula Ale on			THE LEAST			
9 2 :	7 ms 1= 10		1	MERRING HE & MINE	Property 19 1	- 1		- 1	72,14444	N ARREST THERE IN	200
	-				IBRAM 2 4 SAA		4		207.1300	of the same of the same of	00
8			- 2	DEPMANE MIES PERME			and the same			THE WATER APPEAR	
			14.	DATES TOTALLE SAME	一 1 4107 帝				五日	ACT AND ACT	
SALE:			117	PATTINE FEMALE - ME							
					THERE BY				72	5_20_52	
E.					Battastin 27:						
			-					-			
Die Control				THE THE ATT	S STORE - THE	STEEL STORE			T. Time	の下に三十二	·=
E-			717	EW PE EDMERN	10 Tal -10 40000	nt richt		0			
					19 - 500	The Street of th					
	-	THE THE	71	SAME SHAFE DAME		Inc	n there	F F =	WE THE WAY	C	
THE TH THE 28-	3	THE ST. BALL		THEY I THINK THOSE	100	72 fam 172	H IPME	1-20 =- Zi	THE THE PER		
			-	of our Tarrier To Like the			-		B 2651	2 LDW280-1	7004
	and the		23	LAS BOR BARE	FR E TO	Terror - Tru HE	_ = 11	= -44		Z DESCRIPTION	135
AS DASH NI LESSE		* -				A COUNTY		-			
TATA TAMES ME TARET		Winter of the			There was made	who was at		i	THE WE	- Sales	二年 一
1-6		CC 17, 64,			4 <	-					


1 mas 9-1100





0 1





GRUMMAN A-RCRA ENGINEERING CORP.
COURT IDEN NO. 2512
ENGINEERING ORDER


GRUMMAN A-RCRA ENGINEERING CORP.
COMPRES LEO 280 100/182
COMPRES LOWER 1819 NO. LOWE


FOR THE PART NO'S NOTED *, EFFECTIVE LM-10(40)
THRU LM-14(44) ~ REVISE THE NEXT ASSEMBLIES
ADD: LTA-11(23) & LTA-3 % -1(460) EFFECTIVITY FOR NAS
(QTY. REMAINS THE SAME AS THAT OF LM-10(40))


144 121 1/1 25


PART NOX	N/A (WAS)	N/A (NOW)	DWG. TITLE	CHG. NO.
LDW280-17906-13	LUW280-23542	LDW280-60542	SEE DWG.	84
IN/290-10679 D	LDW280-23544	1 DW280-60541		87
18638-13 -2,-3	LDW280-23543. LDW280-23544	LDW280-60543 LDW280-60544	SEE DWG.	A5


		** ***			_•	- 1	- 17	٠,	٠.	,	•		
Nation	O ES Su CO	ti 3 tikalis cing	- IV	rc	D 3850		G.56			-4.4.	ج		(5)
FOR EXTEND	FLOWER	DECKS TANKS	FOR	JAF.	N/A (NON) WAS) LDW2 NO(40) THE N(40) EFF	50-255 LH-14	92 - 2 (44)	3543	1280 p = 2	544 A	142 - 605 Dlaú lia h	3	BELFASE MIS 71501
6-00ts	urecomie T	SHOW CHAPTER	in a	\$15-1516(0) (3)	APP FORED BY	PSF	I		Sull	4/61		ATT TO	
A TIVITY I,O	ASC CONF NO	SHE COMIN UNIT NO	1		MC.L.	asti	8-16-67			8/1/69	Holy	10/01	The same
-! !1	LM-10(40) THRU		MI // N	Merchan	Promis State		IDV	SWYGHT	SHI'Ad	CHANGER	Challes Starte	HAD)	175
	LMMAN LTA-4(29)	Palolili	1		ENTERED PARTY	Enacted by 10 ao							
149	LITA-SDR 1(40	į t	f , NOILL							LEO 280 M			
10-24-69 R. BEHAN	1/P. THORJUSEN	¥86046 %	ķ	7		·D.	_			GROW	NO 33	5 PL	- 25






















MAS 9-1100


REV SHEET REV					1				FRACTIONS - DECIMALS - ANGLES ± 1/16 ± 020 ± 1/2	CHECKED BY		ER 5-2-66			-	STRAP	. I., NEW YORK	-
SHEET			2.00 3				Ţ		DIMENSIONS ARE IN INCHES. TOLERANCE UNLESS SPECIFIED	DRAWN BY			WEIGHTS	WIMMDEAS 5-9-6	4	GRUMMAN AIRCI		P
SH R			ESCRIPTION		SEE SU	BQ SH			UNLESS OTHERWISE SPECIFIED	CONTRACT I	O. NAS	9-1100		LINE ITEM 1			TATION TYPE II	
PART NO.					GAEC SCH NO.		OR ENO ITEM	PART NO.			GAEC SCH N	O. OR END IT	PART NO.LDW 280-		17928-11 	GAEC SCH NO.	OR ENO ITES	
MODEL OR END ITEM		NEXT ASSY			OR SER NO.	NO.	REQU PER MODULE	MODEL OR END ITEM	NEXT ASSY		OR SER NO.		F MODEL ON LI		NEXT ASSY	OR SER NO.	REOD P	
														LM		LDW280-2557		
			_				1							LM		LDW 280-2551	Z LTA-8(18)	
				_			\dashv							LM		LDW 280-2557	2 LM-1(31)	
_							-						+	-			+-	-
					Ξ		\neg						_				-	
							士											
		\Box					\dashv						-	-		-		
													1 -					
							\dashv										1.	
							\Rightarrow											
					_		1						1					
		\dashv					\pm				<u>Š</u>							
_							\Rightarrow				LDW280							
_							#											
		=					7				-17928							
		-					\mp				0							
											\vdash							




 O_{1}



O 1 MAS 9-1100



O 1 NAS 9-1100





MAS 8-1100

 \bigcirc


0


-







O 1 NAS 9-1100














3/3












P1 5 GROUP NO.335


-LIAISON


SECTION VDI


X1441


ISSUED BY VINCENT CHRISTINE / W TRAUT


























MANUFACTURING OPERATIONS
UNLESS OTHERWISE SPECIFIED
HOTES DEDIED \(\sqrt{APPLY} \) TO this two

